

SEC8 SCOUT (es) & SEC8 (es)

ELECTRIC WINCHES

BEST WORKING RANGE PERFORMANCE IN THE INDUSTRY.

These 8,000 pound winches feature a series wound motor and best in class performance. These winches redefine value and performance in the 8,000 pound winch class.



8,000 LB (3629 kg)
PN: 77-53141W



8,000 LB (3629 kg)
PN: 77-50141W

SPECIFICATIONS:

Rated line pull	8000 lbs (3629 Kg)
Gear Train	3 Stage Planetary
Gear Ratio	152:1
Motor	Series Wound, 4.8 hp (3.6 KW), 12 V
Control Pendant	Power In, Power Out Remote, 12' (3.7 m)
Dimensions (LxWxH)	21.50" X 6.25" X 8.00" (546.1 mm X 158.8 mm X 203.2 mm)
Rope	5/16" X 100' (7.94 mm X 28.5 m)
Cable	5/16" X 100' (7.94 mm X 30.5 m)
Drum Size (Diameter and length)	2.5" X 9" (63.5 mm X 228.6 mm)
Net weight (Rope)	57.5 lbs (37 kg)
Net weight (Cable)	70 lbs (31.75 kg)
Bolt Pattern	4 Bolt Pattern, 4.5" x 10" (114.3 mm X 254 mm)

FEATURES:

- 4.8 HP Series Wound Motor
- Fast Line Speeds
- Rugged Planetary Gear Sets
- Automatic Load Holding Brake
- Clockable Gear Housing
- 100' of Synthetic Rope or Steel Cable
- Fully Sealed
- Submersible, 500 Amp Solenoid
- Marine Grade Remote Control Connectors
- Corrosion Resistant
- Stainless Steel Hardware

PERFORMANCE:

Line Pull		Line Speed		Motor Current
lb	kg	fpm	mpm	amps @ 12 V
0	0	26	7.9	95
2000	907	20	6	175
4000	1814	14	4.3	240
6000	2722	12	3.8	295
8000	3629	10.8	3.3	370

