

# SEC95 (es)

ELECTRIC WINCHES

## With Synthetic Rope

9,500 LB (4309 kg)  
PN: 76-53246BW



## With Steel Cable

9,500 LB (4309 kg)  
PN: 76-50246BW



### FEATURES:

- Powerful Series Wound Motor
- Fast Line Speeds
- Rugged Planetary Gear Sets
- Automatic Load Holding Brake
- Clockable Gear Housing
- 100' of Synthetic Rope or Steel Cable
- Fully Sealed
- Submersible, 500 Amp Solenoid
- Marine Grade Remote Control Connectors
- Corrosion Resistant
- Stainless Steel Hardware

### PERFORMANCE:

Line Pull		Line Speed		Motor Current
lb	kg	fpm	mpm	amps @ 12 V
0	0	25.7	7.8	85
2000	907	15.1	4.6	150
4000	1814	10.5	3.2	210
6000	2722	7.9	2.4	270
8000	3629	5.9	1.8	320
9500	4309	4.3	1.3	375

### SPECIFICATIONS:

Gear Train	3 Stage Planetary
Gear Ratio	212:1
Motor	Series Wound, 4.8 hp (3.6 kw), 12 Volt, 24 volt available
Control Pendant	Power In, Power Out Remote, 12' (3.7 m)
Dimensions (LxWxH)	22.25" X 6.25" X 8.00" (565.2 mm X 158.8 mm X 203.2 mm)
Rope	3/8" X 100' (9.53 mm X 30.5 m)
Cable	3/8" X 100' (9.53 mm X 30.5 m)
Drum Size (Diameter and length)	2.5" X 9" (63.5 mm X 228.6 mm )
Net weight (Rope)	67 lbs (30.39 kg)
Net weight (Cable)	92 lbs (41.73 kg)
Bolt Pattern	4 Bolt Pattern, 4.5" x 10" (114.3 mm X 254 mm)