

# SEC12 (es)

ELECTRIC WINCH

## PROVEN WINCH DESIGN AT AN UNMATCHED VALUE.

Heavy duty series wound motors and rugged planetary gear sets are the backbone of this winch series. With robust controls, fully sealed solenoids and body, and an integrated kill switch, the SEC12 and SEC95 is a proven winch design at an unmatched value.

### With Synthetic Rope

12,000 LB (5443 kg)  
PN: 76-53251BW



### With Steel Cable

12,000 LB (5443 kg)  
PN: 76-50251BW



#### FEATURES:

- Powerful Series Wound Motor
- Fast Line Speeds
- Rugged Planetary Gear Sets
- Automatic Load Holding Brake
- Clockable Gear Housing
- 100' of Synthetic Rope or Steel Cable
- Fully Sealed
- Submersible, 500 Amp Solenoid
- Marine Grade Remote Control Connectors
- Corrosion Resistant
- Stainless Steel Hardware

#### PERFORMANCE:

Line Pull		Line Speed		Motor Current
lb	kg	fpm	mpm	amps @ 12 V
0	0	23	7	90
2000	907	12.8	3.9	145
4000	1814	9.7	3.0	185
6000	2722	7.9	2.4	230
8000	3629	7.1	2.2	270
10000	4536	5.1	1.6	315
12000	5443	4.5	1.4	370

#### SPECIFICATIONS:

Gear Train	3 Stage Planetary
Gear Ratio	296:1
Motor	Series Wound, 4.8 hp (3.6 kw), 12 Volt, 24 volt available
Control Pendant	Power In, Power Out Remote, 12' (3.7 m)
Dimensions (LxWxH)	22.25" X 6.25" X 8.00" (565.2 mm X 158.8 mm X 203.2 mm)
Rope	3/8" X 100' (9.53 mm X 30.5 m)
Cable	3/8" X 100' (9.53 mm X 30.5 m)
Drum Size (Diameter and length)	2.5" X 9" (63.5 mm X 228.6 mm)
Net weight (Rope)	67 lbs (30.39 kg)
Net weight (Cable)	92 lbs (41.73 kg)
Bolt Pattern	4 Bolt Pattern, 4.5" x 10" (114.3 mm X 254 mm)